

Vertical Balers / Compactors

BRAND  **BACE**  MADE IN USA
BALER AND COMPACTOR EQUIPMENT

Designed and manufactured with the highest quality materials and components to deliver long life, superior reliability, optimal levels of safety and the lowest maintenance cost.



V3016HD

LIQUID EXTRACTOR BALER
Combines draining and baling refuse beverage or liquid containers in one step.



V32

OCC AND PLASTIC FILM BALER
Compact design, economical and dependable; perfect when work space is limited.



V43DC

DRUM CRUSHER
Reduces storage space up to 80%; eases handling and lower transportation costs.

Description and Specifications for each model are detailed on page 2, 3 and 4.

Please, contact us if you need more information or a detailed quote.

January 2018

V3016HD – Vertical Baler Compactor Liquid Extractor

Combines draining and baling refuse beverage or liquid containers in one step.

- The right baler for non-ferrous metals, cans and containers in residual liquid applications.
- Help increase your recycling time of refuse containers over seven times faster than manually extracting the liquids.
- Can make a single bale from up to 4000 aluminum beverage cans and up to 2000 plastic beverage bottles.
- Includes a system to capture the liquid waste and divert it to an approved drain.

SPECIFICATIONS	
PERFORMANCE	
Nominal Bale	Size 30 x 16" x 24"
Bale Weight	Up to 250 lbs
Bale Volume	6.7 cu. ft.
No. of Bale Tie Slots	5
Compact Force lbs - Based on Factory Set (psi)	62,203
Average Cycle Time	49 Seconds
Loading Height	41"
Ejector System	Semi-Automatic
Full Bale Light	Standard
HYDRAULIC / ELECTRICAL	
Motor HP	15
Voltage 3 Phase	208V, 230V, 480V
Full Load Amps (A = Amps)	48A, 42A, 21A
Pump GPM	12
Factory Set System Pressure	PSI 2200
Cylinder Bore x Stroke	6" x 48"
Hydraulic Reservoir Capacity	22 gal

ADDITIONAL HYDRAULIC / ELECTRICAL CONFIGURATIONS ARE AVAILABLE.
PLEASE CALL FOR MORE INFORMATION.

STANDARD POWER UNITS AVAILABLE			
MOTOR HP	VOLTAGE	FULL LOAD AMPS	POWER SUPPLY REQUIRED
15HP-DRY-3PH	208V	48	100
5HP-DRY-3PH	230V	42	100
5HP-DRY-3PH	460/480V	21	60

OPTIONAL ACCESSORIES AVAILABLE.

Please, contact us if you need more information or a detailed quote.



IDEAL FOR:

- Waste Handlers and Collectors
- Recycling Centers
- Distribution Centers
- Companies e Institutions
- Food Packaging Plants
- Bottling and Beverage Plants
- Hospitals and Care Centers
- Schools and Universities
- Grocery Stores
- Others

V32 – Vertical Baler, OCC and Plastic Film

The smallest baler for OCC and Plastic Film.

- Compact design and economical, yet dependable.
- Space saving without sacrificing quality and durability.
- Perfect when work space is limited.

SPECIFICATIONS	
PERFORMANCE	
Nominal Bale	36" x 24" x 30"
Bale Weight	Up to 250 lbs
Bale Volume	15 cu. ft.
No. of Bale Tie Slots	4
Compact Force lbs - Based on Factory Set (psi)	12,016
Average Cycle Time	40 Seconds
Loading Height	35.5"
Ejector System	Semi-Automatic
Full Bale Light	Optional
HYDRAULIC / ELECTRICAL	
Motor HP	3
Voltage 3 Phase	208V, 230V, 480V
Full Load Amps (A = Amps)	13A, 12A, 8A
Pump GPM	2.8
Factory Set System Pressure	PSI 1700
Cylinder Bore x Stroke	3" x 30"
Hydraulic Reservoir Capacity	9 gal

ADDITIONAL HYDRAULIC / ELECTRICAL CONFIGURATIONS ARE AVAILABLE.
PLEASE CALL FOR MORE INFORMATION.

STANDARD POWER UNITS AVAILABLE			
MOTOR HP	VOLTAGE	FULL LOAD AMPS	POWER SUPPLY REQUIRED
15HP-DRY-3PH	208V	13	30
5HP-DRY-3PH	230V	12	30
5HP-DRY-3PH	460/480V	8	20

OPTIONAL ACCESSORIES AVAILABLE.



IDEAL FOR:

- Waste Handlers and Collectors
- Recycling Centers
- Distribution Centers
- Companies e Institutions
- Food Packaging Plants
- Botteling and Beverage Plants
- Hospitals and Care Centers
- Schools and Universities
- Grocery Stores
- Others

Please, contact us if you need more information or a detailed quote.

V43DC – Drum Crusher

Designed to compress a 55-Gallon Drum to 5" high.

- Over 50,000 pounds of crushing force.
- Reduces Storage Space up to 80%.
- Eases Handling and lower Transportation Costs.
- Can be converted into an inside-the-drum waste compactor for Oil Filters, Smaller Drums or Containers.
- Drum Piercing: Punch a hole through the top or all the way through the bottom.
- Oil Sight Gauge - Oil level at a glance.
- UL/CUL Listed Control Panels.
- Heavy Duty Controls - NEMA 4 rated pushbutton controls with key-lockable start switch.

SPECIFICATIONS	
PERFORMANCE	
Compact Force lbs - Based on Factory Set (psi)	50,893
Platen Pressure	56 PSI
Average Cycle Time	49 Seconds
HYDRAULIC / ELECTRICAL	
Motor HP	10
Voltage 3 Phase	208V, 230V, 480V
Full Load Amps (A = Amps)	30A, 28A, 14A
Pump GPM	10.5
Factory Set System Pressure	PSI 1800
Cylinder Bore x Stroke	6" x 42"
Hydraulic Tank Capacity	22 gal

ADDITIONAL HYDRAULIC / ELECTRICAL CONFIGURATIONS ARE AVAILABLE. PLEASE CALL FOR MORE INFORMATION.

STANDARD POWER UNITS AVAILABLE			
MOTOR HP	VOLTAGE	FULL LOAD AMPS	POWER SUPPLY REQUIRED
10 HP-DRY-3PH	208V	30	60
10 HP-DRY-3PH	230V	28	60
10 HP-DRY-3PH	460/480V	14	30

OPTIONAL ACCESSORIES AVAILABLE.



IDEAL FOR:

- Waste Handlers and Collectors
- Recycling Centers
- Distribution Centers
- Others

OPTIONAL ACCESSORIES:

- Explosion-Proof Controls: Non-sparking hydraulic or pneumatic control circuits.
- Alternate Compaction Head (CH): Compact waste into the drum with the same machine.
- Bolt-On Crush Plate (CP): For quick change-out between crushing and compacting.
- RAM BOTTOM LOCK Control: Keep plastic drums crushed.
- Air Filtration and Ventilation: Control dust and vapors.
- Liquid Containment: Control spills or leftover residue.
- Other Special Custom Options available.

Please, contact us if you need more information or a detailed quote.