

## Vertical Balers / Compactors

BRAND   **MADE IN USA**

**Designed and manufactured with the highest quality materials and components to deliver long life, superior reliability, optimal levels of safety and the lowest maintenance cost.**



### **V3016HD**

**LIQUID EXTRACTOR BALER**  
Combines draining and baling refuse beverage or liquid containers in one step.



### **V32**

**OCC AND PLASTIC FILM BALER**  
Compact design, economical and dependable; perfect when work space is limited.



### **V43DC**

**DRUM CRUSHER**  
Reduces storage space up to 80%; eases handling and lower transportation costs.

*Description and Specifications for each model are detailed on page 2, 3 and 4.*

*Please, contact us if you need more information or a detailed quote.*

June 2018

# V3016HD – Vertical Baler Compactor Liquid Extractor

**Combines draining and baling refuse beverage or liquid containers in one step.**

- The right baler for non-ferrous metals, cans and containers in residual liquid applications.
- Help increase your recycling time of refuse containers over seven times faster than manually extracting the liquids.
- Can make a single bale from up to 4000 aluminum beverage cans and up to 2000 plastic beverage bottles.
- Includes a system to capture the liquid waste and divert it to an approved drain.

SPECIFICATIONS	
PERFORMANCE	
Nominal Bale	Size 30 x 16" x 24"
Bale Weight	Up to 250 lbs
Bale Volume	6.7 cu. ft.
No. of Bale Tie Slots	5
Compact Force lbs - Based on Factory Set (psi)	62,203
Average Cycle Time	49 Seconds
Loading Height	41"
Ejector System	Semi-Automatic
Full Bale Light	Standard
HYDRAULIC / ELECTRICAL	
Motor HP	15
Voltage 3 Phase	208V, 230V, 480V
Full Load Amps (A = Amps)	48A, 42A, 21A
Pump GPM	12
Factory Set System Pressure	PSI 2200
Cylinder Bore x Stroke	6" x 48"
Hydraulic Reservoir Capacity	22 gal

ADDITIONAL HYDRAULIC / ELECTRICAL CONFIGURATIONS ARE AVAILABLE.  
PLEASE CALL FOR MORE INFORMATION.

STANDARD POWER UNITS AVAILABLE			
MOTOR HP	VOLTAGE	FULL LOAD AMPS	POWER SUPPLY REQUIRED
15HP-DRY-3PH	208V	48	100
5HP-DRY-3PH	230V	42	100
5HP-DRY-3PH	460/480V	21	60

OPTIONAL ACCESSORIES AVAILABLE.

**Please, contact us if you need more information or a detailed quote.**



### IDEAL FOR:

- Waste Handlers and Collectors
- Recycling Centers
- Distribution Centers
- Companies e Institutions
- Food Packaging Plants
- Bottling and Beverage Plants
- Hospitals and Care Centers
- Schools and Universities
- Grocery Stores
- Others

# V32 – Vertical Baler, OCC and Plastic Film

## The smallest baler for OCC and Plastic Film.

- Compact design and economical, yet dependable.
- Space saving without sacrificing quality and durability.
- Perfect when work space is limited.

SPECIFICATIONS	
PERFORMANCE	
Nominal Bale	36" x 24" x 30"
Bale Weight	Up to 250 lbs
Bale Volume	15 cu. ft.
No. of Bale Tie Slots	4
Compact Force lbs - Based on Factory Set (psi)	12,016
Average Cycle Time	40 Seconds
Loading Height	35.5"
Ejector System	Semi-Automatic
Full Bale Light	Optional
HYDRAULIC / ELECTRICAL	
Motor HP	3
Voltage 3 Phase	208V, 230V, 480V
Full Load Amps (A = Amps)	13A, 12A, 8A
Pump GPM	2.8
Factory Set System Pressure	PSI 1700
Cylinder Bore x Stroke	3" x 30"
Hydraulic Reservoir Capacity	9 gal

ADDITIONAL HYDRAULIC / ELECTRICAL CONFIGURATIONS ARE AVAILABLE.  
PLEASE CALL FOR MORE INFORMATION.

STANDARD POWER UNITS AVAILABLE			
MOTOR HP	VOLTAGE	FULL LOAD AMPS	POWER SUPPLY REQUIRED
15HP-DRY-3PH	208V	13	30
5HP-DRY-3PH	230V	12	30
5HP-DRY-3PH	460/480V	8	20

OPTIONAL ACCESSORIES AVAILABLE.



### IDEAL FOR:

- Waste Handlers and Collectors
- Recycling Centers
- Distribution Centers
- Companies e Institutions
- Food Packaging Plants
- Botteling and Beverage Plants
- Hospitals and Care Centers
- Schools and Universities
- Grocery Stores
- Others

**Please, contact us if you need more information or a detailed quote.**

# V43DC – Drum Crusher

**Designed to compress a 55-Gallon Drum to 5" high.**

- Over 50,000 pounds of crushing force.
- Reduces Storage Space up to 80%.
- Eases Handling and lower Transportation Costs.
- Can be converted into an inside-the-drum waste compactor for Oil Filters, Smaller Drums or Containers.
- Drum Piercing: Punch a hole through the top or all the way through the bottom.
- Oil Sight Gauge - Oil level at a glance.
- UL/CUL Listed Control Panels.
- Heavy Duty Controls - NEMA 4 rated pushbutton controls with key-lockable start switch.

SPECIFICATIONS	
<b>PERFORMANCE</b>	
Compact Force lbs - Based on Factory Set (psi)	50,893
Platen Pressure	56 PSI
Average Cycle Time	49 Seconds
<b>HYDRAULIC / ELECTRICAL</b>	
Motor HP	10
Voltage 3 Phase	208V, 230V, 480V
Full Load Amps (A = Amps)	30A, 28A, 14A
Pump GPM	10.5
Factory Set System Pressure	PSI 1800
Cylinder Bore x Stroke	6" x 42"
Hydraulic Tank Capacity	22 gal

ADDITIONAL HYDRAULIC / ELECTRICAL CONFIGURATIONS ARE AVAILABLE. PLEASE CALL FOR MORE INFORMATION.

STANDARD POWER UNITS AVAILABLE			
MOTOR HP	VOLTAGE	FULL LOAD AMPS	POWER SUPPLY REQUIRED
10 HP-DRY-3PH	208V	30	60
10 HP-DRY-3PH	230V	28	60
10 HP-DRY-3PH	460/480V	14	30

OPTIONAL ACCESSORIES AVAILABLE.



### IDEAL FOR:

- Waste Handlers and Collectors
- Recycling Centers
- Distribution Centers
- Others

### OPTIONAL ACCESSORIES: (Additional cost)

- Explosion-Proof Controls: Non-sparking hydraulic or pneumatic control circuits.
- Alternate Compaction Head (CH): Compact waste into the drum with the same machine.
- Bolt-On Crush Plate (CP): For quick change-out between crushing and compacting.
- RAM BOTTOM LOCK Control: Keep plastic drums crushed.
- Air Filtration and Ventilation: Control dust and vapors.
- Liquid Containment: Control spills or leftover residue.
- Other Special Custom Options available.

**Please, contact us if you need more information or a detailed quote.**